



US009AFXSX-001-02

N:NY9T
L:LCP
P:PBT

1:5u"FULL AU N180u"MIN
2:3u"FULL AU N180u"MIN
3:10u"FULL AUN180u"MIN
4:15u"FULL AUN180u"MIN
5:30u"FULL AUN180u"MIN

REV.	ECN. NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN

NETS:

1.MECHANIAL;
MATING:35N MAX
WITHDRAWAL:10N.MIN
DURABILTY:1500 CYCLES.MIN.

2.ELECTRICAL:

CURRENT:100..mA. MAX
VOLTAGE:20mV.MAX
WITHSTANDING.VOLTAGE:100v.AC

CONTACT.PESISTANCE:30MΩMax-50mΩ
INSULATION PESISTANE:1000MΩ MIN

3.ENVIPONEMNTAL

TEMPERATURE.RANCE-55° C--+85° C

4.PRODUCT:MEET FOR ROHS.STANDAR

ITEM	PART,NAME	Q'TY	METERIAL
1	HOUSING	1	PBT+30%GF.BLUE
2	COVER	1	PBT+30%GF.BLUE
3	CONTACT1	5	C2680R-EH.GOLD.XU" salt:24h
4	CONTACT2	4	C5191R-H.GOLD.Xu" salt:24h
5	SHELL	1	C2680R-H.NI.80U" MIN

INTENDED USE	UNIT : mm	华捷科技有限公司
PART NO.	FINISH	
TOLERANCES	MAT'L	FILE NO. US009AFXSX-001-02 TITLE: USB3.0 AF 线端 APPD: CHKD: DR: Gary.Lee DWG NO.: REC. CONNECTOR SCALE 1;1 SHEET 1 OF 1 REV. A