

PAGE		115		BY		CHK		REVISION RECORD MODIFICATIONS		DATE		REV.	
				ALLEN				RELEASE TO PRODUCTION		2007,8,2		1.0	

Pin1

A Type

Pin1

B Type

Pin1

C Type

2.00±0.10

PIN0.50X0.20

2.00XNo.ofContacts-2.00

2.00XNo.ofPositions+0.50

4.30

2.50

3.00

4.00

A,B Type

2.00

3.00

2.00

C Type

2.00±0.05

4.00±0.05

Ø1.00

Ø0.08

A Type

2.00±0.05

4.00±0.05

Ø0.80

Ø1.00

B Type

2.00±0.05

2.00±0.05

Ø0.80

Ø1.00

C Type

2.00±0.05

2.00±0.05

Ø0.80

Ø1.00

C Type

Recommended PCB Layout
(PCB TOLERANCE±0.05)

P

S

2

S

4

3

B

-

1

X

X

X

B

X

-

X

No.of contacts per row(02-40)

G:Gold flash S:Selective
GA:Gold 5u" SA:Selective5u"
GB:Gold 10u" SB:Selective10u"
GC:Gold 20u" SC:Selective20"
GD:Gold 30u" SD:Selective30"
Ti:TiN Plated TE:TiN200u"

Bi:BlackInsulator

P.C.B Layout
AA Type
BB Type
CC Type

L:RoHS+P.B.T
U:RoHS+Nylon6T

APPRO	CHECK	DRAWN	PART NO.	PS2S43B-1XXXXBX-X			DESCRIPTION			
			ITEM NO.							
			DRAW NO.							
			UNIT	mm	SCALE	no				
			TOLER		NO.		Tel:0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com			