


PAGE	256	BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV
		ALLE		RELEASE TO PRODUCTION	2007,8,27	1.0

SPECIFICATIONS
Current Ration: 0.5A AC,DC
Voltage Ration: 30V AC,DC
Temperature Range:-25°C ~ + 85°C
Contact Resistance:20m£Max,
Insulation Resistance:100M£Min.
Withstanding Voltage: 200V AC/minute
Contacts:Phosphor Brnze/Tin-plated
Material:Nylon 46,UL94V-0
Color:Natural(Beige)

PART NΠ.	Dimensions			
LAKI NU.	А	В		
0800IDC-02W-U	0.80	2.40		
0800IDC-04W-U	2.40	4.00		
0800IDC-08M-N	5,60	7.20		
0800IDC-10W-U	7,20	8.80		
0800IDC-12W-U	8.80	10.40		
0800IDC-14W-U	10.40	12.00		
0800IDC-15W-U	11.20	12.80		
0800IDC-16W-U	12.00	13.60		
0800IDC-17W-U	12.80	14.40		
0800IDC-50M-N	15.20	16.80		







Part No:0800IDC-XXW-U

APPRO	CHECK	DRAWN	PART NO. Part No. 0800IDC-XXW-U			-XXW-U	DESCRIPTION		
			ITEM NO.	'EM NO.			DESCRIPTION	Vicontec	
			DRAW NO.					(IGORTEC	
			UNIT	$_{ m mm}$	SCALE	$\mathbf{no}$			
			TOLER		NO.		Tel: 0769 22020068 Fax: 0769 2202	20069 E—mail: sales@vigortec.com	