

PAGE	266	BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		ALLEN		RELEASE TO PRODUCTION	2007,9,3	1.0

Wire Range	Insulation O.D	Material	Finish	Qty/reel
AWG#26-#30	1.00mm(max)	Phosphor Bronze	Tin-plated	15,000pcs

SEC:A-A SEC:B-B

Part No.:1252-T-L

SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25℃ ~ +85℃
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 100mΩ Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66, UL94V-0
 Pantone Color: 7529~7530C

PART NO.	Dimensions	
	A	B
1252H-02TW-L	1.25	4.15
1252H-03TW-L	2.50	5.40
1252H-04TW-L	3.75	6.65
1252H-05TW-L	5.00	7.90
1252H-06TW-L	6.25	9.15
1252H-07TW-L	7.50	10.40
1252H-08TW-L	8.75	11.65
1252H-09TW-L	10.00	12.90
1252H-10TW-L	11.25	14.15
1252H-11TW-L	12.50	15.40
1252H-12TW-L	13.75	16.65
1252H-13TW-L	15.00	17.90
1252H-14TW-L	16.25	19.15
1252H-15TW-L	17.50	20.40

Part No.:125H-1XXW-L

APPRO	CHECK	DRAWN	PART NO.	Part No.:1252H-1XXW-L			DESCRIPTION	
			ITEM NO.					
			DRAW NO.					
			UNIT	mm	SCALE	no		
			TOLER		NO.			
Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com								