




PartNo.: 1255-T-L






Wire Range	Insulation O.D	Material	Finish	Qty/reel
AWG#26-#32	0.90mm(max)	Phosphor Bronze	Gold-flash	15,000pcs

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 100mΩ Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66, UL94V-0
 Color: Black

PartNo.: 1255H-XXB-L

PART NO.	Dimensions		
	A	B	C
1255H-02B-L	1.25	3.80	6.00
1255H-03B-L	2.50	5.05	7.25
1255H-04B-L	3.75	6.30	8.50
1255H-05B-L	5.00	7.55	9.75
1255H-06B-L	6.25	8.80	11.00
1255H-08B-L	8.75	11.30	13.50
1255H-10B-L	11.25	13.80	16.00
1255H-15B-L	17.50	20.05	22.25
1255H-20B-L	23.75	26.30	28.50
1255H-25B-L	30.00	32.55	34.75
1255H-30B-L	36.25	38.80	41.00



APPRO

CHECK

DRAWN

PART NO.

Part No.:1255H-XXB-L

ITEM NO.

DRAW NO.

UNIT

mm

SCALE

no

TOLER

NO.

DESCRIPTION



Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com