





Wire Range	Insulation O.D	Material	Finish	Qty/reel
AWG#24-#30	1.30mm(max)	Brass	Tin-plated	10,000pcs



SEC:A-A






SEC:B-B




SEC:C-C


PartNo.:2005-T-L




SEC:A-A



SEC:B-B



SEC:C-C



SEC:D-D


Wire Range	Insulation O.D	Material	Finish	Qty/reel
AWG#24-#30	1.30mm(max)	Brass	Tin-plated	10,000pcs

PartNo.: 2005-RT-L


SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25℃ ~ +85℃
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000mΩ Min
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66, UL94V-0
 Color: Natural(White)

CONTACT	Dimensions	
	A	B
02	2.00	5.20
03	4.00	7.20
04	6.00	9.20
05	8.00	11.20
06	10.00	13.20
07	12.00	15.20
08	14.00	17.20
09	16.00	19.20
10	18.00	21.20
11	20.00	23.20
12	22.00	25.20
13	24.00	27.20
14	26.00	29.20
15	28.00	31.20
16	28.00	31.20







Circuit1




P.C.B LAYOUT

PartNo.:2005H-XXW-L





Circuit1



P.C.B LAYOUT

PartNo.:2005RH-XXW-L



APPRO

CHECK

DRAWN

PART NO.

Part No.2005RH-XXW-L

ITEM NO.

DRAW NO.

UNIT

mm

SCALE

no

TOLER

NO.

DESCRIPTION



Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com