









SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 500V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 100mΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66, UL94V-0
 Pantone Color: 153C


PART NO.	Dimensions	
	A	B
2504R-02TR-L	2.50	5.00
2504R-03TR-L	5.00	7.50
2504R-04TR-L	7.50	10.00
2504R-05TR-L	10.00	12.50
2504R-06TR-L	12.50	15.00
2504R-07TR-L	15.00	17.50
2504R-08TR-L	17.50	20.00
2504R-09TR-L	20.00	22.50
2504R-10TR-L	22.50	25.00
2504R-11TR-L	25.00	27.50
2504R-12TR-L	27.50	30.00
2504R-13TR-L	30.00	32.50
2504R-14TR-L	32.50	35.00
2504R-15TR-L	35.00	37.50



7P~15P



P.C.B LAYOUT



PartNo.: 2504R-XXTR-L

APPRO	CHECK	DRAWN	PART NO.	Part No.:2504R-XXTR-L	DESCRIPTION	
			ITEM NO.			
			DRAW NO.			
			UNIT	mm		
			TOLER	NO.		
Tel:0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com						