

PAGE	308	BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		ALLEN		RELEASE TO PRODUCTION	2007,9,4	1.0

Part No	Wire Range	Insulation O.D	Material	Finish	Qty/reel
2505-TP-L	AWG#22-#30	1.90mm(max)	Phosphor Bronze	Tin-plated	10,000pcs
2505-TB-L	AWG#22-#30	1.90mm(max)	Brass	Tin-Plated	

Part No.: 2505-T-L

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25℃ ~ +85℃
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000mΩ Min
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66, UL94V-0
 Color: Natural(White)

PART NO.	Dimensions	
	A	B
2505H-02W-L	2.50	7.00
2505H-03W-L	5.00	9.50
2505H-04W-L	7.50	12.00
2505H-05W-L	10.00	14.50
2505H-06W-L	12.50	17.00
2505H-07W-L	15.00	19.50
2505H-08W-L	17.50	22.00
2505H-09W-L	20.00	24.50
2505H-10W-L	22.50	27.00
2505H-11W-L	25.00	29.50
2505H-12W-L	27.50	32.00
2505H-13W-L	30.00	34.50
2505H-14W-L	32.50	37.00
2505H-15W-L	35.00	39.50

Circuit1

Part No.: 2505H-XXW-L

APPRO	CHECK	DRAWN	PART NO.	Part No.:2505H-XXW-L	DESCRIPTION	
			ITEM NO.			
			DRAW NO.			
			UNIT	mm		
			TOLER		NO.	

Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com