



SPECIFICATION

Current Rate: 1 AMP
 Insulation Resistance: 500mΩ Min
 Contact Resistance: 30mΩ Max
 Dielectric voltage: 500V AC for one minute
 Operation Temperature: -55°C to +105°C

MATERIAL


Insulator: Polyester, UL94v-0
 Standard: P.B.T
 Contact Pin: Brass



Mate flat cable 1.27mm

No. of Contacts	Dim. A	Dim B	Dim C
6	11.2	5.00	4.00
8	13.20	7.00	6.00
10	15.20	9.00	8.00
12	17.20	11.00	10.00
14	19.20	13.00	12.00
16	21.20	15.00	14.00
18	23.20	17.00	16.00
20	25.20	19.00	18.00
22	27.20	21.00	20.00
24	29.20	23.00	22.00
26	31.20	25.00	24.00
28	33.20	27.00	26.00
30	35.20	29.00	28.00
32	37.20	31.00	30.00
34	39.20	33.00	32.00

No. of Contacts	Dim. A	Dim B	Dim C
36	41.20	35.00	34.00
38	43.20	37.00	36.00
40	45.20	39.00	38.00
44	49.20	43.00	42.00
48	53.20	47.00	46.00
50	55.20	49.00	48.00
54	59.20	53.00	52.00
56	61.20	55.00	54.00
60	65.20	59.00	58.00
62	67.20	61.00	60.00
64	69.20	63.00	62.00
68	73.20	67.00	66.00
80	85.20	79.00	78.00
100	105.20	99.00	98.00



APPRO	CHECK	DRAWN	PART NO.	DESCRIPTION	
			ITEM NO.		
			DRAW NO.		
			UNIT	mm	SCALE no
			TOLER	NO.	
Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com					

