





PAGE	3	BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		ALLEN		RELEASE TO PRODUCTION	2007,7,26	1.0

SPECIFICATION
 Curerent Rate: 0.5 AMP
 Insulation Rrsistance: 100mΩMin
 Conract Resistance: 30mΩMax
 Dielectric voltage: 50V AC for one minute
 Operation Temperature: -20℃to +105℃

MATERIAL
 Insulator: Polyester,UL94v-0
 ©Standard: Nylon 46
 Conract Pin: Phosphor Bronze
 Contact Plated: Gold Plated




Recommended PCB Layout
 (PCB TOLERANCE±0.05)



CIRCUITS	DIMENSION			
	A	B	C	D
10	4.60	2.00	4.10	3.10
12	5.10	2.50	4.60	3.60
14	5.60	3.00	5.10	4.10
16	6.10	3.50	5.60	4.60
18	6.60	4.00	6.10	5.10
20	7.10	4.50	6.60	5.60
22	7.60	5.00	7.10	6.10
24	8.10	5.50	7.60	6.60
26	8.60	6.00	8.10	7.10
30	9.60	7.00	9.10	8.10
32	10.10	7.50	9.60	8.60
36	11.10	8.50	10.60	9.60
40	12.10	9.50	11.60	10.60
50	14.60	12.00	14.10	13.10
60	17.10	14.50	16.60	15.60

• After Mating Height

MATING	MALE P/N	FEMALE P/N
2.50	BTB05MD17-XX	BTB05MD17-XX
3.00	BTB05MD22-XX	BTB05MD22-XX
3.50	BTB05MD22-XX	BTB05MD27-XX
4.00	BTB05MD27-XX	BTB05MD27-XX
4.50	BTB05MD27-XX	BTB05MD32-XX
5.00	BTB05MD42-XX	BTB05MD22-XX
5.50	BTB05MD42-XX	BTB05MD27-XX
6.00	BTB05MD47-XX	BTB05MD27-XX
6.50	BTB05MD47-XX	BTB05MD32-XX



APPRO	CHECK	DRAWN	PART NO.	BTB05MDXX-XXGNXX-U			DESCRIPTION BOARD TO BOARD MALE 0.5mm H=1.7/2.2/2.7/4.2/4.7mm	
			ITEM NO.					
			DRAW NO.					
			UNIT	mm	SCALE	no		
			TOLER		NO.		Tel: 0769 22020068 Fax: 0769 22020069 E-mail: sales@vigortec.com	